

Model	Intake Mode	Bore/Stroke (mm)	Displacement (L)	Rated Power (kW)	Rated Speed (r/min)	Max. Torque/Speed (N·m)/(r/min)	Min. Fuel Consumption (g/kWh)	Idle Speed (rpm)	Dimension (mm)	Weight (kg)	Fuel System	Emission Level
BF6M1015	Turbocharged	132 ×145	11.906	223~240	1900/2100	1420/1300	209	600	1043×932×1174	850	In-line Pump	National II

Model	Intake Mode	Bore/Stroke (mm)	Displacement (L)	Rated Power (kW)	Rated Speed (r/min)	Max. Torque/Speed (N·m)/(r/min)	Min. Fuel Consumption (g/kWh)	Idle Speed (rpm)	Dimension (mm)	Weight (kg)	Fuel System	Emission Level
BF6M1015C	Turbocharged Inter-cooled	132 ×145	11.906	273~300	1900/2100	1978/1200	200	600	1043×932×1174	850	In-line Pump	National II

Model	Intake Mode	Bore/Stroke (mm)	Displacement (L)	Rated Power (kW)	Rated Speed (r/min)	Max. Torque/Speed (N·m)/(r/min)	Min. Fuel Consumption (g/kWh)	Idle Speed (rpm)	Dimension (mm)	Weight (kg)	Fuel System	Emission Level
BF6M1015CP	Turbocharged Inter-cooled	132 ×145	11.906	300~330	1900/2100	1876/1300	202	600	1043×932×1174	850	In-line Pump	National II

Model	Intake Mode	Bore/Stroke (mm)	Displacement (L)	Rated Power (kW)	Rated Speed (r/min)	Max. Torque/Speed (N·m)/(r/min)	Min. Fuel Consumption (g/kWh)	Idle Speed (rpm)	Dimension (mm)	Weight (kg)	Fuel System	Emission Level
-------	-------------	------------------	------------------	------------------	---------------------	---------------------------------	-------------------------------	------------------	----------------	-------------	-------------	----------------

				(kW)		(N·m)/(r/min)	(g/kWh)	(rpm)				
BF8M1015C	Turbocharged Inter-cooled	132 ×145	15.874	364~400	1900/2100	2640/1200	200	600	1151×955×1174	1060	In-line Pump	National II

Model	Intake Mode	Bore/Stroke (mm)	Displacement (L)	Rated Power (kW)	Rated Speed (r/min)	Max. Torque/Speed (N·m)/(r/min)	Min. Fuel Consumption (g/kWh)	Idle Speed (rpm)	Dimension (mm)	Weight (kg)	Fuel System	Emission Level
BF8M1015CP	Turbocharged Inter-cooled	132 ×145	15.874	400~440	1900/2100	2500/1300	211	600	1151×955×1174	1060	In-line Pump	National II

Model	Intake Mode	Bore/Stroke (mm)	Displacement (L)	Rated Power (kW)	Rated Speed (r/min)	Max. Torque/Speed (N·m)/(r/min)	Min. Fuel Consumption (g/kWh)	Idle Speed (rpm)	Dimension (mm)	Weight (kg)	Fuel System	Emission Level
TCD2015V06	Turbocharged Inter-cooled	132 ×145	11.906	240~360	2100	2080/1300	202	600	1077× 932×1141	1020	Unit Pump	National III

Model	Intake Mode	Bore/Stroke (mm)	Displacement (L)	Rated Power (kW)	Rated Speed (r/min)	Max. Torque/Speed (N·m)/(r/min)	Min. Fuel Consumption (g/kWh)	Idle Speed (rpm)	Dimension (mm)	Weight (kg)	Fuel System	Emission Level
TCD2015V08	Turbocharged	132 ×145	15.874	350~500	2100	2890/1400	208	600	1250×932×1172	1245	Unit	National

	Inter-cooled										Pump	III
--	--------------	--	--	--	--	--	--	--	--	--	------	-----

Model	Intake Mode	Bore/Stroke (mm)	Displacement (L)	Rated Power (kW)	Rated Speed (r/min)	Max. Torque/Speed (N·m)/(r/min)	Min. Fuel Consumption (g/kWh)	Idle Speed (rpm)	Dimension (mm)	Weight (kg)	Fuel System	Emission Level
TCD12.0V6	Turbocharged Inter-cooled	132 ×145	11.906	240~390	2100	2130/1400	193	600	1140×945×1168	995	High-Pressure Common Rail	National IV

Model	Intake Mode	Bore/Stroke (mm)	Displacement (L)	Rated Power (kW)	Rated Speed (r/min)	Max. Torque/Speed (N·m)/(r/min)	Min. Fuel Consumption (g/kWh)	Idle Speed (rpm)	Dimension (mm)	Weight (kg)	Fuel System	Emission Level
TCD16.0V8	Turbocharged Inter-cooled	132 ×145	15.874	350~520	2100	2890/1400	199	600	1395×945×1196	1260	High-Pressure Common Rail	National IV